

Data Sheet

ENC400/V46/100/0013

Titan Pro - 40.3.VL1.T – Titan Power 400A 400v Distribution to 3 x 125/3, 3 x 63/3, 4 x 32/3, 6 x 16/1. Main MCCB, RCBOs.

Warranty Period - 36 Months Warranty on all Parts and Manufacturing Defects

Product Overview - IP44, IK10, Double Insulated.

Enclosure: V46/100 Shockproof polyethylene enclosure, water resistant up to IP67, Impact Resistance IK10

Enclosure Dimensions: 1000 x 600 x 600mm (H x W x D)

Inlet: 1 x 400A 400v L1+L2+L3+N+E, IP67 6h Powerlock Syntax Panel Drain Set by Valentini

1 x 400A 400v L1+L2+L3+N+E, IP67 6h Powerlock Syntax Panel Source Set by Valentini – Loop through
(No Protection)

Power Socket Outlets:

3 x 125A 400v 3P+N+E, IP67 6h Panel socket by Mennekes

3 x 63A 400v 3P+N+E, IP67 6h Panel socket by Mennekes

4 x 32A 400v 3P+N+E, IP44 6h Panel socket by Mennekes

6 x 16A 230v P+N+E, IP44 6h Panel socket by Mennekes – Wired 2 Per Phase

Protection:

Incomer: 1 x Main 400A 4P MCCB, C Curve with Rotary Trip Switch by ABB – **Protects all sockets**

Outlet Protection:

3 x 125A 4P MCB C curve by Doepke - Protects 125A 400v Sockets

3 x 63A 4P MCB C curve by Doepke - Protects 63A 400v Sockets

4 x 32A /30mA 4P RCBO Type A, C curve by Doepke - Protects 32A 400v Sockets

6 x 16A /30mA 2P RCBO Type A, C Curve by Doepke - Protects 16A 230v Sockets

Extra:

1 x Rayleigh D440 Digital 3 Phase Meter (Volts/Amps)

1 x set of 3 x green phase neon indicators

1 x 12mm earthing stud

If an order is confirmed based on the above quotation/specification, you have agreed with the quoted price and design layout. Bespoke products cannot be returned without a charge.



If an order is confirmed based on the above quotation/specification, you have agreed with the quoted price and design layout. Bespoke products cannot be returned without a charge.

T: 01752 858 043 | E: info@titanpower.co.uk | W: www.titanpower.co.uk
Unit 22 Trevol Business Park, Torpoint, Cornwall, United Kingdom, PL11 2TB