

Data Sheet

ENC400/V45/100/0080

Titan Plus – 40.3.VL1.P - Titan Plus 400A 400v Distribution to 6 x 63A 400v, 6 x 32A 400v, RCD + MCB

Warranty Period - 24 Months Warranty on all Parts and Manufacturing Defects

Product Overview - IP44, IK10, Double Insulated.

Enclosure: V46/100 polyethylene enclosure, water resistant up to IP67, Impact Resistance IK10

Enclosure Dimensions: 1312 x 690 x 690mm (H x W x D)

Inlet: 1 x 400A 400v L1+L2+L3+N+E, IP67 PowerSyntax Panel Drain by Valentini

Socket Outlets:

6 x 32A 400v 3P+N+E, IP44 6h Panel Socket by Mennekes

6 x 63A 400v 3P+N+E, IP67 6h Panel Socket by Mennekes

Protection:

Incomer: 1 x Main 400A 4P Isolator with Rotary Handle (lockable in the OFF position) by ABB – **Breaks all protected sockets**

Outlet Protection:

3 x (1 x 63A /30mA 4P RCD Type A + 2 x 32A 4P MCB, C Curve) – Protects 32A 400v Sockets

6 x 63A /300mA 4P RCD Type A + 6 x 63A 4P MCB, C Curve – Protects 63A 400v Sockets

Extras:

1 x Set of 3 x Green Phase Neon Indicators

1 x Protective Steel Lifting Frame



If an order is confirmed based on the above quotation/specification, you have agreed with the quoted price and design layout. Bespoke products cannot be returned without a charge.