

Data Sheet

ENC125/415/L1/T

Titan Plus – 12.3.V8.P - Titan Plus 125A 400v Distribution to 1 x 63/3, 6x 32/1, 18 x 16/1. Main Isolator, RCD + MCB

Warranty Period - 24 Months Warranty on all Parts and Manufacturing Defects

Product Overview - IP44, IK10, Double Insulated.

Enclosure: V45/80 polyethylene enclosure, water resistant up to IP67, Impact Resistance IK10

Enclosure Dimensions: 770 x 475 x 415mm (H x W x D)

Inlet: 1 x 125A 400v 3P+N+E, IP67 6h Panel Inlet by Mennekes

Socket Outlets:

18 x 16A 230v P+N+E, IP44 6h Panel Socket by Mennekes – wired 6 per phase

6 x 32A 230v P+N+E, IP44 6h Panel Socket by Mennekes – wired 2 per phase

1 x 63A 400v 3P+N+E, IP67 6h Panel Socket by Mennekes

Protection:

Incomer: 1 x Main 125A 4P Isolator switch by Doepke – **Breaks all protected sockets**

Outlet Protection:

3 x (1 x 40A /30mA 4P RCD Type A + 6 x 16A 1P MCB, C Curve) – Protects 16A 230v Sockets

2 x (1 x 40A /30mA 4P RCD Type A + 3 x 32A 1P MCB, C Curve) – Protects 32A 230v Sockets

1 x 63A 4P MCB, C Curve – Protects 63A 400v Sockets

Extras:

1 x Set of 3 x Green Phase Neon Indicators

If an order is confirmed based on the above quotation/specification, you have agreed with the quoted price and design layout. Bespoke products cannot be returned without a charge.



If an order is confirmed based on the above quotation/specification, you have agreed with the quoted price and design layout. Bespoke products cannot be returned without a charge.

T: 01752 858 043 | E: info@titanpower.co.uk | W: www.titanpower.co.uk
Unit 22 Trevol Business Park, Torpoint, Cornwall, United Kingdom, PL11 2TB