

Data Sheet

ENC125/415/T

Titan Plus – 12.3.V4.P – Titan Plus 125A 400v Distribution to 3 x 32/1, 12 x 16/1. Main Isolator + RCDs + MCBs

Warranty Period - 24 Months Warranty on all Parts and Manufacturing Defects

Product Overview - IP44, IK10, Double Insulated.

Enclosure: V45/48 polyethylene enclosure, water resistant up to IP67, Impact Resistance IK10 **Enclosure Dimensions:** 460 x 475 x 415mm (H x W x D)

Inlet: 1 x 125A 400v 3P+N+E, IP67 6h Panel Inlet by Mennekes

Socket Outlets:

12 x 16A 230v P+N+E, IP44 6h Panel Socket by Mennekes – wired 4 per phase 3 x 32A 230v P+N+E, IP44 6h Panel Socket by Mennekes – wired 1 per phase

Protection:

Incomer: 1 x Main 125A 4P Isolator switch by Doepke - Breaks all protected sockets

Outlet Protection:

2 x (1 x 40A /30mA 4P RCD Type A + 6 x 16A 1P MCB, C Curve) – Protects 6 x 16A 230v Sockets per RCD. 1 x 40A /30mA 4P RCD Type A + 3 x 32A 1P MCB, C Curve – Protects 32A 230v Sockets.

Extras:

1 x Set of 3 x Green Phase Neon Indicators

If an order is confirmed based on the above quotation/specification, you have agreed with the quoted price and design layout. Bespoke products cannot be returned without a charge.





If an order is confirmed based on the above quotation/specification, you have agreed with the quoted price and design layout. Bespoke products cannot be returned without a charge.