

Data Sheet:

ENC32/415/V45/24/0010/RM

Portable In-Line Remote Monitor, rated 32 Amps / 400v

32.3.V2.3 - **Titan Pro** 32A 400v Remote Monitoring Unit to 1 x 32A 400v Socket

Monitoring designed to display Live and Historical Data of power usage, Measuring Amps, kWh, Volts, Frequency. Panel Meter and Remote PC Display via 2/4G Data Link.

Warranty Period - 36 Months Warranty on all Parts and Manufacturing Defects

Product Overview – IP67, IK10, Double Insulated.

Enclosure: V45/24 Polyethylene Enclosure, Water Resistant **up to** IP67, Impact Resistance IK10
Enclosure Dimensions: 215 x 475 x 415mm (H x W x D)

Inlet: 1 x 32A 400v 3P+N+E, IP67 Appliance Inlet by Mennekes

Outlet: 1 x 32A 400v 3P+N+E, IP67 Panel Socket by Mennekes – loop through (**No protection**)

Monitoring:

1 x Rayleigh RI-D440 Multifunction Analyser

1 x Rayleigh RI-EC-LITE Series GSM Communication 2/4G Gateways with Antenna

1 x 20MB Capped Data Bundle Complete with Network Roaming SIM Card - Valid for **24 months**

Extras:

3 x Green Phase Neon Indicators

