

Data Sheet

Aug 2023

ENC63/415/V45/48/0057/RM

Portable Power Distribution with Remote Monitoring, rated 32 Amps / 400v

63.3.V4.3 - **Titan Pro** 63A 400v Distribution to 4 x 32/3. Isolator + RCBOs + Remote Monitoring

Monitoring designed to display Live and Historical Data of power usage, Measuring Amps, kWh, Volts, Frequency, available for each socket outlet + overall usage. Panel Meter and Remote PC Display via 2/4G Data Link.

Warranty Period - 36 Months Warranty on all Parts and Manufacturing Defects

Product Overview - IP44, IK10, Double Insulated.

Enclosure: V45/48 Shockproof polyethylene enclosure, water resistant up to IP67

Enclosure Dimensions: 460 x 475 x 415mm (H x W x D)

Inlet: 1 x 63A 400v 3P+N+E, IP67 Appliance Inlet by Mennekes

Socket Outlets:

4 x 32A 400v 3P+N+E, IP44 Panel Socket by Mennekes

Protection:

Incomer: 1 x Main 100A 4P Isolator Switch by Doepke – **Breaks all Protected Sockets**

Outlet Protection:

4 x 32A /30mA 4P RCBO Type A, C Curve by Doepke – Protects 32A sockets

Monitoring:

1 x Rayleigh RI-D480 Multifunction Analyser – 12 x Single & 4 x Three Phase

1 x GSM Communication Gateways with Antenna

4 x 3 Phase CT Pick Up Coils, for data on each socket & overall usage

1 x 20MB Capped Data Bundle Complete with SIM Card - Valid for **24 months**

Extras:

3 x Green Phase Panel Neons

1 x 8mm Earth Stud

