

Data Sheet

Aug 2023

ENC125/415/V45/36/0011/RM

Portable In-Line Remote Monitor, rated 125 Amps / 400v

125.3.V3.3 - Titan Pro 125A 400v Distribution to 125/3 Socket. No protection + Remote Monitoring

Monitoring designed to display Live and Historical Data of power usage, Measuring Amps, kWh, Volts, Frequency, available for each socket outlet + overall usage. Panel Meter and Remote PC Display via 2/4G Data Link.

Warranty Period - 36 Months Warranty on all Parts and Manufacturing Defects

Product Overview – IP67, IK10, Double Insulated.

Enclosure: V45/36 Polyethylene Enclosure, Water Resistant **up to** IP67, Impact Resistance IK10

Enclosure Dimensions: 335 x 475 x 415mm (H x W x D)

Inlet: 1 x 125A 400v 3P+N+E, IP67 Appliance Inlet by Mennekes

Outlet: 1 x 125A 400v 3P+N+E, IP67 Panel Socket by Mennekes – loop through (No protection)

Monitoring:

1 x Rayleigh RI-D440 Multifunction Analyser

1 x Rayleigh RI-EC-LITE Series GSM Communication 2/4G Gateways with Antenna

1 x 3 Phase CT Pick Up Coils, for data on overall usage

1 x 20MB Capped Data Bundle Complete with Network Roaming SIM Card - Valid for **24 months**

Extras:

1 x 12mm Earthing Stud

3 x Green Phase Neon Indicators

