

Data Sheet:

ENC63/415/V45/48/0062

Titan Plus – 63.3.V4.2 - Titan Plus 63A 400v Distribution to 3 x 32/1, 12 x 16/1 Sockets. Isolator + RCD + MCBs

Warranty Period - 24 Months Warranty on all Parts and Manufacturing Defects

Product Overview – IP44, IK10, Double Insulated.

Enclosure: V45/48 Polyethylene Enclosure, Water Resistant up to IP67, Impact Resistance IK10 Enclosure Dimensions: $480 \times 500 \times 420$ mm (H x W x D)

Inlet: 1 x 63A 400v 3P+N+E, IP67 6h Appliance Inlet by Mennekes

Socket Outlets:

12 x 16A 230v P+N+E, IP44 6h Panel Socket by Mennekes – 4 per Phase 3 x 32A 230v P+N+E, IP44 6h Panel Socket by Mennekes – 1 per Phase

Protection:

Incomer: 1 x Main 100A 4P Isolator Switch by Doepke - Breaks all protected sockets

Outlet Protection:

2 x 40A /30mA 4P RCD Type A + 12 x 16A 1P MCB C Curve by Doepke – Protects 16A 230v Sockets. 1 x 40A /30mA 4P RCD Type A + 3 x 32A 1P MCB C Curve by Doepke – Protects 32A 230v Sockets.

Extras:

- 3 x Green Phase Neon Indicators
- 1 x 8mm Earthing Stud



If an order is confirmed based on the above quotation/specification, you have agreed with the quoted price and design layout. Bespoke products cannot be returned without a charge.

> T: 01752 858 043 | E: info@titanpower.co.uk | W: www.titanpower.co.uk Unit 22 Trevol Business Park, Torpoint, Cornwall, United Kingdom, PL11 2TB